

Printing date 12/18/2024 Reviewed on 12/18/2024

#### 1 Identification

· Product identifier

· Trade name: PAINT GUARD

· Article number: K-331

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kaady Chemical Corp. 2545 SW SPRING GARDEN ST STE 120 PORTLAND, OR 97219 +1-510-562-9788 www.kaadychemical.com

· Information department: Product safety department

· Emergency telephone number:

chemtrec 800-424-9300

acct# 12158

### 2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- Hazard-determining components of labeling:

Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides 2-butoxvethanol

· Hazard statements

Harmful if swallowed.

· Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)

Health = 1

Fire = 0 Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 0

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	· Dangerous	components:	
Γ	541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	<10%
ſ	111-76-2	2-butoxyethanol	<10%
Ī	61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	<10%

### Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of 1910.1200 of 29 CFR 1910.1200 Trade Secrets.

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

- 2)





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 2)

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with the skin or eyes.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid contact with the eyes, skin and clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppn
64-19-7	acetic acid	5 ppm
10043-52-4	calcium chloride	12 mg/n
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* pp
64-19-7	acetic acid	35 ppm
10043-52-4	calcium chloride	130 mg/r
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** pp
64-19-7	acetic acid	250 ppm
		(Contd. on pag

US





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

 10043-52-4
 calcium chloride
 (Contd. of page 3)

 790 mg/m³
 790 mg/m³

#### 7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

All ventilation should be disigned in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 20 ppm

BEI, A3

#### · Ingredients with biological limit values:

### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 4)

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

· General Information

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

· Information on basic physical and chemical properties

· Appearance:		
Form:	Liquid	
Color:	Amber colored	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	

· Flash point:	150 °C (302 °F)
· Flammability (solid, gaseous):	Not applicable.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Not determined.

Explosion limits:

Decomposition temperature:

Lower: Not determined.
Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density (Specific Gravity): Not determined.

(Contd. on page 6)





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

		(Contd. of pag
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	-* <b>%</b>	
Water:	Proprietary %	
VOC content:	-* %	
	_*	
Solids content:	-* %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	1,432–1,617 mg/kg
Inhalative	LC50/4 h	157 mg/l
111-76-2 2-hutovyothanol		

111-70-2 2-buloxyellianoi			
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	

(Contd. on page 7)





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 6)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eve: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information: Harmful
- · Carcinogenic categories
- IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

3

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

- 11





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 7)

UN-Number		
DOT, IMDG, IATA	not regulated	
UN proper shipping name DOT, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)



Page 9/10

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Conta. or page 6)
NL

· TLV (Threshold Limit Value)

Carcinogenic categories

111-76-2 2-butoxyethanol

None of the ingredients is listed.

· EPA (Environmental Protection Agency)

- 111-76-2 2-butoxyethanol A3 67-63-0 propan-2-ol A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling:

Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides

2-butoxyethanol

· Hazard statements

Harmful if swallowed.

· Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- · Date of preparation / last revision 12/18/2024 / -
- · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)



Page 10/10

## Safety Data Sheet acc. to OSHA HCS

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: PAINT GUARD

(Contd. of page 9)

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

00