



Printing date 12/18/2024 Reviewed on 12/18/2024

1 Identification

· Product identifier

Trade name: WEATHER REPELLANT

· Article number: K-200A

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier:
Kaady Chemical Corp.
2545 SW SPRING GARDEN ST STE 120
PORTLAND, OR 97219
+1-510-562-9788
www.kaadychemical.com

- · Information department: Product safety department
- Emergency telephone number: CHEMTREC 800-424-9300

ACCT# 12158

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

 Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides

2-butoxyethanol

· Hazard statements

Harmful if swallowed.

Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 1)

- · Classification system:
- NFPA ratings (scale 0 4)

Health = 1

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 0

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	· Dangerous components:			
61789-77-	3 Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	<10%		
111-76-	2 2-butoxyethanol	<10%		
541-02-	6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	<10%		
67-63-	0 propan-2-ol	<5%		

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of 1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with the skin or eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid contact with the eyes, skin and clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:	60 000
111-76-2 2-butoxyethanol	60 ppm
67-63-0 propan-2-ol	400 ppm
100-52-7 benzaldehyde	4 ppm
141-78-6 ethyl acetate	1,200 ppn
140-11-4 benzyl acetate	30 ppm
628-63-7 pentyl acetate	100 ppm
PAC-2:	
111-76-2 2-butoxyethanol	120 ppm
67-63-0 propan-2-ol	2000* ppn
100-52-7 benzaldehyde	9.9 ppm
141-78-6 ethyl acetate	1,700 ppm
140-11-4 benzyl acetate	330 ppm
	670 ppm

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd.	of	page	3)
---------	----	------	----

PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
100-52-7	benzaldehyde	59 ppm
141-78-6	ethyl acetate	10000** ppm
140-11-4	benzyl acetate	2,000 ppm
628-63-7	pentyl acetate	4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

All ventilation should be disigned in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

The time time, are careful concataonte mayo no minem expectate mine.	
111-76-2 2-butoxyethanol	
PEL Long-term value: 240 mg/m³, 50 ppm Skin	
REL Long-term value: 24 mg/m³, 5 ppm Skin	
TLV Long-term value: 20 ppm BEI, A3	
67-63-0 propan-2-ol	
PEL Long-term value: 980 mg/m³, 400 ppm	
•	(Contd. on page 5

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 4)

REL | Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 400 ppm Long-term value: 200 ppm

BEI, A4

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Dark blue
Odor: Characteristic

(Contd. on page 6)

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

		(Contd. of pa
Odor threshold:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density (Specific Gravity):	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	-* %	
Water:	PROPRIETARY %	
VOC content:	-* %	
	_*	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
ATE (Acu	te Toxicity	y Estimate)	
Oral	LD50	1,188–1,348 mg/kg	
Inhalative	LC50/4 h	220 mg/l	

111-76-2	111-76-2 2-butoxyethanol			
Oral	LD50	1,200 mg/kg (ATE)		
		1,480 mg/kg (rat)		
Dermal	LD50	400 mg/kg (rab)		
67-63-0 p	67-63-0 propan-2-ol			
Oral	LD50	5,045 mg/kg (rat)		
Dermal	LD50	12,800 mg/kg (rabbit)		
Inhalative	LC50/4 h	30 mg/l (rat)		

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information: Harmful
- · Carcinogenic categories

· IARC (Int	ternational Agency for Research on Cancer)	
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
140-11-4	benzyl acetate	3
97-53-0	Eugenol	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

(Contd. on page 8)

Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information	
· UN-Number · DOT, IMDG, IATA	not regulated
· UN proper shipping name · DOT, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
Transport in bulk according to Annex In MARPOL73/78 and the IBC Code	II of Not applicable.
· UN "Model Regulation":	not regulated

- U





Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol
- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL

· TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

A3 A4

67-63-0 propan-2-ol 140-11-4 benzyl acetate

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







Printing date 12/18/2024 Reviewed on 12/18/2024

Trade name: WEATHER REPELLANT

(Contd. of page 9)

- · Signal word Warning
- Hazard-determining components of labeling:

Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides 2-butoxyethanol

2-buloxyelilarioi

· Hazard statements

Harmful if swallowed.

Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- · Date of preparation / last revision 12/18/2024 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4